

VF10 Visual Fault Locator

Key Benefits

- Pocket-size designs resists impacts and weather
- 2.5mm universal connector
- Features Pulse and CW modes
- Illuminates distances up to 10km



The Deviser VF10 is a pocket-sized visual fault locator, perfect for identifying breaks, bends, splices, or faulty connectors in an optical fiber installation - as well as other causes of signal loss.

Specifications

Measurements	Specifications
Wavelength	650 ±10nm
Emitter type	FP
Output power	> 10mW
Operation modes	CW; 1Hz
Interface	PC, 2.5mm universal connector
Environment	Operation temperature [-10 ~ +60°C]; Storage temperature [-20 ~ +70°C]
Battery life	~5 hours at 700mA/h; 2x AAA batteries
Dimensions	5.1" x 1.2" x 0.7" (130mm x 30mm x 18mm)
Weight	< 4.5oz (120g)

©2017 Deviser Instruments Incorporated. 780 Montague Expressway, Suite 701, San Jose, CA 95131. All rights reserved. Specifications subject to change without notice. All product and company names are trademarks of their respective corporations. Deviser Instruments manufacturing facilities are ISO 9001 certified. Do not reproduce, redistribute, or repost without written permission from Deviser Instruments. VF10 170904