

CFP2-ACO Passive Loopback Module

ML4030-ACO

CFP2-ACO Loopback module

(4x32G) Interconnects



Key Features

- Supports 4x32G
- CFP2-ACO MSA Form Factor
- MSA compliant MDIO slave
- Built with advanced PCB material
- Custom memory maps
- MSA compliant functionality
- Temperature Monitor and alarms warning
- Programmable Power dissipation up to 12W(can be customized for higher power)
- Superior SI performance
- Designed for 32G Analog Coherent
- Matched trace length on all 4 lanes
- MDIO slave interface compliant with IEEE 802.3 Clause 45
- Programmable MSA memory pages
- RX_LOS-Alarm driven by TX_DIS control or MDIO register
- 3 status LED Indicator
- Insertions counter
- Hot Pluggable module
- Cutoff temperature preventing module overheating

Ordering information ML4030-ACO

Superior Integrity and Performance

Summary

CFP2-ACO Passive Loopback Module **ML4030-ACO**, is designed to provide an efficient and easy method of characterizing and testing 4x32G CFP2 ports.

The **ML4030-ACO** comes packaged in a MSA compliant shell housing offering excellent heat dissipation. It can be programmed to different power levels through an MDIO interface, thus emulating all CFP2-ACO power classes.

Transmit data from the host is electrically routed, (internal to the loopback module), to the receive data outputs and back to the host. It provides an economical way to exercise CFP2-ACO ports during R&D validation, production testing, and field testing.

Applications

- 4x32G Electrical module testing and characterization
- CFP2-ACO Port compliant testing

North America

48521 Warm Springs Blvd. Suite 310
Fremont, CA 94539
USA
+1 510 573 6388

Worldwide

Houmal Technology Park
Askarieh Main Road
Houmal, Lebanon
+961 5 941 668

Asia

14F-5/ Rm.5, 14F., No 295
Sec.2, Guangfu Rd. East Dist.,
Hsinchu City 300, Taiwan (R.O.C)
+886 3 5744 591