

OFI-20A Optical Fiber Identifier

- ◆ Fiber types: 250µm, 900µm, 2mm/3mm jacketed fiber
- ◆ Non-destructive detection
- ◆ Indication of signal presence, strength and direction
- ◆ CW/MOD tones detection
- ◆ Buzzer indication
- ◆ Handheld & sturdy
- ◆ CE, FCC certificates



OFI-20A can detect optical signal presence, type and direction anywhere on fibers during a optical network deployment, maintenance or troubleshooting. With non-destructive macro-bend detection technology, it introduces no damage to tested fiber or interference to the service on fiber. OFI-20A is capable of identifying wide-spectrum signals (such as signals in CATV system) and can be used in SONET/SDH & DWDM systems tests.

Specifications

Model	OFI-20A
Wavelength	800~1700nm
Detector Type	InGaAs
Signal Type	CW, 270Hz±5%, 1kHz±5%, 2kHz±5%
Display	Signal presence / strength / direction, MOD frequency, Low battery
Detect Sensitivity ⁽¹⁾	-40dBm~+5dBm
Insertion Loss	H 0.25~H 0.9: 0.1dB; H 2.0~H 2.5: 0.5dB; H 2.5~H3.0: 1.0 dB
Fiber Type	250µm bare fiber, 900µm/ 2mm/3mm jacketed fiber
Battery	9V Alkaline Battery
Battery Life	≥6 hours
Operating Temperature	-20 ~ 50°C
Storage Temperature	-40 ~70°C
Relative Humidity	0 ~ 95% (Non-condensing)
Weight	235g
Dimensions (HxWxT)	196x35x30mm

* Specifications subject to change without notice

Note: (1) Typical value at 1310/1550nm

