

BUDGET EASY SET BLOWING MACHINE



OUR TECHNOLOGY YOUR SUCCESS



BDJ Budget EasySet is a set of products including BDJ Budget. The blowing machine is paired with a dedicated drill/drive unit-spare battery included and a customised small stainless steel tripod. The blowing unit is designed **to build the last sections of the FTTH network**. Delivered with special bushings facilitating blowing fiber optic cables from Ø 0.5mm diameter.

BLOWING RANGE:

- CABLE DIAMETER Ø 0,5 - 6 MM
- DUCT DIAMETER Ø 5, 7, 10, 12, 14, 16 MM

ACCESSORIES IN THE SET:

- micro duct cutter,
- set of bushings and micro duct connectors,
- set of gaskets,
- tools,
- spare wheels with removable rubber bands,
- air hose.



TECHNICAL DATA

MICRO CABLE DIAMETER	0,5 – 6 mm
MICRO TUBE DIAMETER	5, 7, 10, 12, 14, 16 mm
BLOWING DISTANCE / MAX	700 m
BLOWING SPEED / MAX	60 m/min
WORK PRESSURE / MAX	15 bar
DIMENSIONS OF THE UNIT (LXWXH)	260 x 100 x 140 mm weight approx. 2kg
DIMENSIONS OF THE TRANSPORT BOX	465 x 400 x 155 mm weight approx. 8kg
AVAILABLE ACCESSORIES	• micro duct cutter • set of bushings and micro duct connectors • set of gaskets • additional tools • spare wheels with removable rubber bands • air hose
REQUIRED COMPRESSOR'S EFFICIENCY	• micro ducts up till 8mm: 0,8m³/min • micro ducts between 8-12mm: 1,0m³/min • micro ducts between 12-15mm: 1,5m³/min
RECOMMENDED COMPRESSOR:	KAESER M17A, ATMOS PB82

**36 MONTHS
WARRANTY**

EQUIPMENT

A SET OF SEALS FOR THE CABLE	with no hole, 1, 2, 3, 4, 5, 6, 7, 8 mm
QUICK CONNECTORS FOR MICRODUCTS (PNEUMATIC)	5, 10, 12, 14, 16 mm 7mm (using 10/7 mm reducer)
REPLACEABLE DRIVE WHEELS	• Drive wheel with flat rubber, • Drive wheel with a rubber groove 2 mm X2, • Drive wheel with a rubber groove 4 mm x2 • Drive wheel with a rubber groove 6 mm x2
SET OF CALIBRATION BALLS	2x: 3mm, 5mm, 7mm, 8mm, 10mm
MICRO TUBES CUTTER 0-25 MM	
SLIDING FLUID FOR FIBER OPTICS PRELUBE 5000 0.24L	
AIR HOSE - 10 M	
LONG ALLEN KEY 2,5 MM	
LONG ALLEN KEY 4 MM	
CORDLESS SCREWDRIVER	
STAINLESS STEEL TRIPOD	